

Approximated Peano Curve. The space-filling process has not been completed.

Figure 1A (Prior Art)



Boustrophedon Path

Figure 1B (Prior Art)



Archimedes Spiral defined by equally distributed points

Figure 1C (Prior Art)



Spiral-like line-based scanning

Figure 1D (Prior Art)



Figure 2A



Figure 2B


computer
system 102A
140
110B
110D
camera 110A
camera 110C
objects 120
manufacturing
apparatus
106
rejected
object 122
REJECTED

Figure 3A



Figure 3B



Figure 3C



Figure 3D



The situation of Lemma 1

Figure 4A



Case (A)

Figure 4B



Case (B)

Figure 4C



Smooth transition between two circles of different radii.

Figure 4D



Smooth transition between two circles of same radius.

Figure 4E



Transition between two unit circles of radius 1. The distance between the circles is sqrt(3)

Figure 4F



Beginning (left) and completion (right) of a scanning scheme where the curvature is below a certain value

Figure 5A



Construction of s2 and the subsequent part of the curve

Figure 5B



Conformal Spiral.

Figure 6


Start
Place Object In Scan Region
702
Determine Characteristic Geometry of Scan Region
704
Generate Conformal Scan Curve Based on Characteristic Geometry
706
Scan Region Using the Conformal Scan Curve
708
Determine One or More Characteristics of the Object
710
Generate Output Indicating the Determined Object Characteristics
712
End

Figure 07



The first 1000 Halton points (left) and randomly chosen points (right)

Figure 8A



Original solution (left) and splined version (right).

Figure 8B


Start
Calculate Low Discrepancy Sequence for Scan Region
902
Calculate a Motion Control Trajectory Based On the Low Discrepancy Sequence
904
Scan Region Using Calculated Motion Control Trajectory
906
Determine Object Characteristics
908
Generate Output Indicating the Determined Object Characteristics
910
End

Figure 9



Definition of I_1, I_2, and I_3

Figure 10



Figure 11A

Figure 11B

Figure 11C


Generate Unbounded Low Discrepancy Point
1222
Apply Boundary Conditions to the Unbounded Low Discrepancy Point to Generate a Bounded Low Discrepancy Point in a Region
1224
Done?
1226
No
Yes
Store Generated Low Discrepancy Sequence of Points Representing a Low Discrepancy Curve in the Region
1228
Output Generated Low Discrepancy Sequence of Points Representing the Low Discrepancy Curve
1230

Figure 12A


Select a Pair of Irrational Numbers (alpha1,alpha2) such that the Sequence ({(n*alpha1)mod1}, {(n*alpha2) mod1}) for all Natural Numbers n is a LDS in the Unit Square.
1202
Select a Length, L, and a Step Rate, epsilon, of the LD Curve in the Unit Square
1204
Initialize Current Length, l, to Zero, and Initialize Current Position (x ,y), (e.g., to (0,0)
1206
Increment x and y and Apply Boundary Conditions at Borders of Unit Square (e.g., Toroidal, Reflectance, or Both), Generating a Low Discrepancy Sequence Point (x_n,y_n)
1208
l < L?
1210
No
Yes
Output Generated Low Discrepancy Sequence of Points Representing the Low Discrepancy Curve
1212

Figure 12B



Beginning of a Low Discrepancy Curve based on a specific Halton Sequency in 2d

Figure 13A



Splined Low Discrepancy Curve coarse search

Figure 13B



Comparison of Conformal Spiral and Low Discrepancy Searching

Figure 13C



Comparison of Travel Distance for Low Discrepancy Search and Conformal Spiral Search

Figure 13D


Start
Calculate Low Discrepancy Sequence for Scan Region
1402
Calculate a Low Discrepancy Curve Based On the Low Discrepancy Sequence
1404
Scan Region Using Calculated Low Discrepancy Curve
1406
Determine Object Characteristics
1408
Generate Output Indicating the Determined Object Characteristics
1410
End

Figure 14



Tiling of the plane and relation to the surface of the unit cube

Figure 15A



Low-discrepancy curve in a ring

Figure 15B



Low Discrepancy Preserving Mapping Function

Figure 15C



Low-discrepancy curve filling the surface of a torus

Figure 15D



Low-discrepancy curve on a sphere
(left) and projections (right)

Figure 16



Figure 17



Surfaces can be scanned efficiently when the term low discrepancy sequence/ curve can be generalized, e.g. based on metrics on the surface.

Figure 18



Splined Low Discrepancy Curve coarse search with refined final approach

Figure 19

Intensity Field Distribution in Search Area



Beam intensity distribution in search area

Figure 20



Location of the Peak

Figure 21A



Initial Final Approach Move

Figure 21B



Error distribution of the estimated peak X coordinate error (left) and Y coordinate error (right)

Figure 21C



Figure 22


Start
Scan Region to Determine An Entry Point and An Exit Point of the Region of Interest
2302
Determine First Local Point of Interest By Scanning Along First Scan Line Between Entry and Exit Points
2304
Calculate Second Scan Line Passing Through First Local Point of Interest and Orthogonal to First Scan Line
2306
Scan Along Second Scan Line to Generate Second Scan Line Measurement Data
2308
Determine Second Local Point of Interest Along Second Scan Line Based on Second Scan Line Measurement Data
2310
Determine Approximate Center of the Region of Interest Based on First and Second Points of Interest
2312
End

Figure 23